



**Mud Hog and Drive Module**

LAND RECLAMATION—  
Modular Processing plant based on  
4272 Mud Hog. High moisture clay is  
reduced from 300mm to 30mm at up to 350  
tonnes per hour for landfill capping.

## Specifications

CRUSHER SIZE	APPROX. WEIGHT (KGS)	APPROX. RPM	APPROX. POWER (KW)	MAX FEED SIZE (MM)	APPROXIMATE CAPACITIES (tonnes per hour — 80% passing square mesh screen)									
					DUTY A - M.H.B. Coal				DUTY B - Wet Iron Ore			DUTY C - Clay/Limestone		
					41mm	25mm	16mm	5mm	50mm	38mm	18mm	50mm	38mm	18mm
2012	1364	1500-2800	15	150	40	23	18	10	45	20-30	10-15	20	15-20	8-10
2420	2727	1000-2200	45	300	160	90	70	35	90	40-60	20-30	40	30-40	16-20
2430	3182	1000-2200	67	300	240	130	105	50	135	60-90	30-45	60	45-60	24-30
2436	3818	1000-2200	75	300	250	140	110	55	175	125-150	75-90	80	70-75	40-50
3624	8636	750-1500	82	450	250	140	110	55	175	125-150	75-90	80	70-75	40-50
3636	10909	750-1500	120	450	360	200	160	80	260	185-225	110-135	120	100-110	60-75
3648	13182	750-1500	157	450	480	270	210	110	350	250-300	150-180	160	140-150	80-100
3660	15773	750-1500	195	450	600	330	260	135	440	310-375	190-225	200	175-190	100-125
4236	12636	600-1000	150	550	540	300	230	130	300	175-200	100-125	120	100-110	60-85
4250	17045	600-1000	217	550	750	430	340	190	350	250-300	150-175	200	150-175	75-100
4266	22273	600-1000	277	550	1000	560	440	240	450	320-385	190-225	250	190-225	80-130
4272	23182	600-1000	300	550	1070	600	470	260	490	350-420	210-245	280	210-245	85-140
5436	15773	600-1000	225	600	900	500	400	200	300	215-255	130-150	175	130-150	50-85
5448	20364	600-1000	300	600	1170	630	530	270	400	280-340	170-200	230	170-200	65-110
5466	23409	600-1000	412	600	1600	870	720	370	550	395-470	240-275	320	240-275	90-155
5472	24409	600-1000	450	600	1750	950	790	400	600	430-515	260-300	350	260-300	100-170
5484	26455	600-1000	525	600	2000	1100	900	460	700	500-600	300-350	400	300-350	115-200

Capacities, power and crusher speed will vary with the physical characteristics of the feed material and must be verified/confirmed by actual testing of customers material. The details contained in this leaflet are for information purposes only and we reserve the right to change product specifications without prior notice.

### APPROXIMATE DIMENSIONS (mm) BARE SHAFT MACHINE ONLY

MODEL	2012	2420	2430	2436	3624	3636	3648	3660	4236	4250	4266	4272	5436	5448	5466	5472	5484
LENGTH	1505	1685	1685	1685	2590	2590	2590	2590	3300	3300	3300	3300	3680	3680	3680	3680	3680
WIDTH*	1195	1730	2595	3110	1645	2465	3285	4110	2110	2930	3865	4215	2120	2825	3885	4235	4940
HEIGHT	1345	1415	1415	1415	2260	2260	2260	2260	2910	2910	2910	2910	3020	3020	3020	3020	3020

\*WIDTH Refers to approximate dimension over shaft.